

## PRODUCT SPECIFICATION

header			
product description	EV 21/20 - Tear off membrane and screw cap. Flow control by built-in regulation and dropless pouring feature.		
product hierarchy	7740/7743		
customer drawing no.	K 5202.01		
neck material	PET	PET	glas
neck finish drawing no.	H 026	PT 29-21 E 08 Ra	VE 29-21 E 02 Na

product properties		
weight	3,8 (±0,1)	grams
resin type		
pouler	LDPE	
screw cap	HDPE	
additional part		
additions		
gasket / liner		
other parts		
packaging		
carton content	3 500	pcs./carton
carton size (LxWxH)	380 x 380 x 580	mm
pallet size	800 x 1200	mm
cartons/palete	20	

storage		
storage temperature		
minimum	10	°C
maximum	35	°C

The delivered closure may be stored for up to 12 months after production date. Direct UV-light during storage must be avoided. The closure should not be subject to penetrating odours or excessive temperature fluctuations.

application		
closure temperature before capping	18 - 28	°C
(closures need to be stored min. 24 hours at required temperature before capping)		
static torque of capping head	-	Nm
	-	inch lbs
head pressure	400	N
head speed		
minimum	-	rpm
maximum	-	rpm

The application of closures as specified herein does not relieve the customer from his province to set the capping equipment as required and to conduct his own compatibility test of the applied closure and the product filled. The bottle neck or orifice must be true to size and in compliance with Bericap neck or orifice drawings.

Technical assistance can be provided by Bericap.