



D	DO	וח	ICT	CDE	CIE	ICA	TION
	KU	יטע		SPE	CIF	ILA	HUN

header					
product description	3440 - Screw closure INTER BEAD Band 48 mm 3 threads				
* *					
product hierarchy					
customer drawing no.	3440				
neck material	PET	PET			
neck finish drawing no.	PT 48-41 V01 Ra	PT 48-41 V01 Rb			

roduct properties			
weight	5,0	gramms	
resin type	·		
pourer	HDPE		
screw cap			
additional part			
additions			
gasket / liner			
other parts			
packaging			
carton content	1 700	pcs./carton	
carton size (LxWxH)	380 x 380 x 580	mm	
pallet size	800 x 1200	mm	
cartons/pallet	20		

torage			
storage temperature		2	
minimum	10	°C	
maximum	28	°C	

The delivered closure may be stored for up to 12 months after production date. Direct UV-light during storage must be avoided. The closure should not be subject to penetrating odours or excessive temperature fluctuations.

pplication		-A		
closure temperature before cappi	ng 18 - 28	°C		
(closures need to be stored min. 24 hours at required temperature before capping)				
static torque of capping head	-	Nm		
	-	inch lbs		
head pressure	-	N		
head speed				
minimum	-	rpm		
maximum	-	rpm		

The application of closures as specified herein does not relief the customer from his province to set the capping equipment as required and to conduct his own compatibility test of the applied closure and the product filled. The bottle neck or orifice must be true to size and in compliance with Bericap neck or orifice drawings.

Technical assistance can be provided by Bericap.