

article name article group TG - AP TG Closure type for bottle neck finish Carrying handle PET PT48-41 V01 Ra PET PT48-41 V01 Rb PET PT48-41 V01 Rb Material: HDPE Weight: 6,800 kg/1000pcs Pet PT48-41 V01 Rb PET PT48-41 V01 Rb Pet PT48-41 V01 Rb PET PT48-41 V01 Rb Material: HDPE Weight: 6,800 kg/1000pcs Pet PT48-41 V01 Rb PET PT48-41 V01 Rb Material: HDPE Weight: 6,800 kg/1000pcs Pet PT48-41 V01 Rb PET PT48-41 V01 Rb Pet PT48-41 V01 Rb PET PT48-41 V01 Rb Material: HDPE Weight: 6,800 kg/1000pcs Pet PT48-41 V01 Rb PET PT48-41 V01 Rb Pet PT48-41 V01 Rb	PRODUCT SPECIFICATION			
closure type for bottle neck finish Carrying handle PET PT48-41 V01 Ra PET PT48-41 V01 Rb PET PT48-41 V01 Rb Material: material / weight Material: HDPE Weight: 6,800 kg/1000pcs Per PT48-41 V01 Rb Per Product Product Product Product Product Product Research Product Prod	article name		article group	
Carrying handle PET PT48-41 V01 Ra PET PT48-41 V01 Rb PET PT48-41 V01 Rb Material: material / weight Material: HDPE Weight: 6,800 kg/1000pcs Packaging Recycling carton 400x600x400 mm (LxBxH) EUR - palette 800x1200 mm Carton/palette 20 Pieces/carton 850 (+/- 1%) closures Storage and application The delivered closures can be stored in stock up to 12 months after production date in order to prevent deterioration from UV light, smell and high temperature variation. Recommended storage temperature max. 35°C. Temperature by application must be: min. 16°C.	TG - AP		TG	
Carrying handle PET PT48-41 V01 Rb material material / weight Material: HDPE Weight: 6,800 kg/1000pcs Packaging Recycling carton 400x600x400 mm (LxBxH) EUR – palette 800x1200 mm Carton/palette 20 Pieces/carton 850 (+/- 1%) closures Storage and application The delivered closures can be stored in stock up to 12 months after production date in order to prevent deterioration from UV light, smell and high temperature variation. Recommended storage temperature max. 35°C. Temperature by application must be: min. 16°C.	closure type			
Material: HDPE Weight: 6,800 kg/1000pcs Packaging Recycling carton 400x600x400 mm (LxBxH) EUR – palette 800x1200 mm Carton/palette 20 Pieces/carton 850 (+/- 1%) closures Storage and application The delivered closures can be stored in stock up to 12 months after production date in order to prevent deterioration from UV light, smell and high temperature variation. Recommended storage temperature: max. 35°C. Temperature by application must be: min. 16°C.	Carrying handle			
Weight: 6,800 kg/1000pcs Packaging Recycling carton 400x600x400 mm (LxBxH) EUR – palette 800x1200 mm Carton/palette 20 Pieces/carton 850 (+/- 1%) closures Storage and application The delivered closures can be stored in stock up to 12 months after production date in order to prevent deterioration from UV light, smell and high temperature variation. Recommended storage temperature: max. 35°C. Temperature by application must be: min. 16°C.	material / weight			
Recycling carton 400x600x400 mm (LxBxH) EUR – palette 800x1200 mm Carton/palette 20 Pieces/carton 850 (+/- 1%) closures Storage and application			DCS	
EUR – palette 800x1200 mm Carton/palette 20 Pieces/carton 850 (+/- 1%) closures Storage and application	Packaging			
The delivered closures can be stored in stock up to 12 months after production date in order to prevent deterioration from UV light, smell and high temperature variation. Recommended storage temperature: max. 35°C. Temperature by application must be: min. 16°C.	EUR – palette800x12Carton/palette20	200 mm		
UV light, smell and high temperature variation. Recommended storage temperature: max. 35°C. Temperature by application must be: min. 16°C.	Storage and application			